



**PRODUCT LINE**  
 LOADERS  
 BACKHOE LOADERS  
 ARTICULATED  
 BACKHOE LOADERS



# VENIERI

**Full Blast.**

The philosophy behind **VF Venieri** activity is realized by the constant research for innovating technical solutions oriented to safety, reliability, stability, performance, operator comfort criteria and permanent technological developments. It is also supported by an excellent after sales service, essential element of its sales strategy, and by a reliable and efficient despatch service granting the spare parts supply to its dealers all over the world.

The Venieri machines are always conceived and designed to operate with the highest flexibility at extreme climatic conditions such as hills, mountains and tropical areas; therefore they are built employing innovative high quality material and components, avoiding as far as possible the electronics. All production and assembly stages are meticulously checked and manufacturing of each single machine is entrusted to a specialized technical team responsible of the product either towards the Clients and the Company.

The hydrostatic transmission, the 10,5 kW/t approx. weight/power net ratio, the balanced weight distribution, the "Z" cinematic front bar linkage and the rear oscillating axle grant **VF Venieri** machines the highest stability, balance and safety easy drive.

The range is up to the task of satisfying the requirements of the single Client, of the great Companies and of the Municipalities; in facts the limited dimensions and the operative agility make the **Venieri's** particularly suitable for the widest uses such as maintenance and construction of roads or buildings, agricultural works, materials stocking and movement.

Our procedures are certified by ISO 9001-VISION 2000.

©2010 VF Venieri



Via Piratello, 106 - 48022 Lugo (RA) ITALY  
 Tel. +39 0545 904411 Fax +39 0545 30389  
 e-mail: info@vf-venieri.com www.vf-venieri.com

**Spare Parts**  
 Tel. +39 0545 904429 Fax +39 0545 24555  
 e-mail: ricambi@vf-venieri.com

The illustrations on the present folder do not necessarily show the product standard version. Data and dimensions described in this folder are not binding. Venieri reserves the right of carrying out possible changes at any time and without previous notice because of its policy of steady development and improvement of the products.



Giacoma Venieri  
 (President)  
*Giacoma Venieri*



## 18.63 / B

LOADER  
"Z-BAR" LINKAGE

	18.63	18.63B
Max. power	225 HP	228 HP
Breakout force	15.620 kg	15.620 kg
Static tipping load - Full turn	13.800 kg	13.800 kg
Bucket min/max	3.5 - 5.0 m <sup>3</sup>	3.5 - 5.0 m <sup>3</sup>
Max. permissible weight	22.000 kg	22.000 kg
Tyres	23.5 - R25	23.5 - R25
Forks load capacity (EN 474-3)	6.600 kg	6.600 kg
Max. speed	40 km/h	40 km/h



## 13.63 / B

LOADER  
"Z-BAR" LINKAGE

	13.63	13.63B
Max. power	177 HP	184 HP
Breakout force	12.000 kg	12.000 kg
Static tipping load - Full turn	9.600 kg	9.600 kg
Bucket min/max	2.7 - 3.5 m <sup>3</sup>	2.7 - 3.5 m <sup>3</sup>
Max. permissible weight	14.150 kg	14.150 kg
Tyres	20.5 - 25	20.5 - 25
Forks load capacity (EN 474-3)	5.600 kg	5.600 kg
Max. speed	40 km/h	40 km/h



## 12.63 / B 11.63 / B

LOADERS - PARALLEL  
"Z-BAR" LINKAGE

	12.63	12.63B	11.63	11.63B
Max. power	150 HP	164 HP	150 HP	164 HP
Breakout force	9.500 kg	9.500 kg	12.800 kg	12.800 kg
Static tipping load - Full turn	8.000 kg	8.000 kg	8.600 kg	8.600 kg
Bucket min/max	2.2 - 3.0 m <sup>3</sup>	2.2 - 3.0 m <sup>3</sup>	2.2 - 3.0 m <sup>3</sup>	2.2 - 3.0 m <sup>3</sup>
Max. permissible weight	13.450 kg	13.450 kg	13.450 kg	13.450 kg
Tyres	20.5 - 25	20.5 - 25	20.5 - 25	20.5 - 25
Forks load capacity (EN 474-3)	5.200 kg	5.200 kg	5.150 kg	5.150 kg
Max. speed	40 km/h	40 km/h	40 km/h	40 km/h



## 10.63 / B 9.63B / C

LOADERS - PARALLEL  
"Z-BAR" LINKAGE

	10.63	10.63B	9.63B	9.63C
Max. power	118 HP	129 HP	118 HP	129 HP
Breakout force	8.000 kg	8.200 kg	8.400 kg	8.600 kg
Static tipping load - Full turn	5.200 kg	5.700 kg	5.500 kg	6.000 kg
Bucket min/max	1.7 - 2.5 m <sup>3</sup>	1.7 - 2.5 m <sup>3</sup>	1.7 - 2.5 m <sup>3</sup>	1.7 - 2.5 m <sup>3</sup>
Max. permissible weight	9.670 kg	9.670 kg	9.670 kg	9.670 kg
Tyres	17.5 - 25	17.5 - 25	17.5 - 25	17.5 - 25
Forks load capacity (EN 474-3)	3.400 kg	3.400 kg	3.700 kg	3.700 kg
Max. speed	34 km/h	40 km/h	34 km/h	40 km/h



## 7.63B / C 5.63B / C

LOADER  
"Z-BAR" LINKAGE

	7.63B	7.63C	5.63B	5.63C
Max. power	105 HP	106 HP	89 HP	79 HP
Breakout force	9.100 kg	7.100 kg	7.000 kg	6.400 kg
Static tipping load - Full turn	4.500 kg	4.700 kg	4.200 kg	4.400 kg
Bucket min/max	1.3 - 2.0 m <sup>3</sup>	1.3 - 2.0 m <sup>3</sup>	1.1 - 1.7 m <sup>3</sup>	1.1 - 1.7 m <sup>3</sup>
Max. permissible weight	7.600 kg	7.600 kg	6.270 kg	6.270 kg
Tyres	405/70 - R24	405/70 - R24	405/70 - R20	405/70 - R20
Forks load capacity (EN 474-3)	3.000 kg	3.000 kg	2.500 kg	2.500 kg
Max. speed	37 km/h	40 km/h	35 km/h	40 km/h



## 4.63G / H 3.63G / H

LOADER  
"Z-BAR" LINKAGE

	4.63G	4.63H	3.63G	3.63H
Max. power	73 HP	72 HP	60 HP	61 HP
Breakout force	5.600 kg	5.600 kg	5.300 kg	5.300 kg
Static tipping load - Full turn	3.500 kg	3.500 kg	3.450 kg	3.450 kg
Bucket min/max	1.0 - 1.3 m <sup>3</sup>	1.0 - 1.3 m <sup>3</sup>	0.8 - 1.1 m <sup>3</sup>	0.8 - 1.1 m <sup>3</sup>
Max. permissible weight	6.090 kg	6.090 kg	5.750 kg	5.750 kg
Tyres	16/70 - 20	16/70 - 20	405/70 R18	405/70 R18
Forks load capacity (EN 474-3)	2.300 kg	2.300 kg	2.120 kg	2.120 kg
Max. speed	30 km/h	28 (35 opt.) km/h	30 km/h	28 (33 opt.) km/h



## Plus 2.63C 2.63C

LOADER  
"Z-BAR" LINKAGE

	2.63C	Plus 2.63C
Max. power	50 HP	50 HP
Breakout force	4.700 kg	5.300 kg
Static tipping load - Full turn	2.700 kg	3.000 kg
Bucket min/max	0.7 - 1.2 m <sup>3</sup>	0.75 - 1.2 m <sup>3</sup>
Max. permissible weight	4.800 kg	4.800 kg
Tyres	12.0/75 - 18	12.0/75 - 18
Forks load capacity (EN 474-3)	1.760 kg	1.920 kg
Max. speed	20 km/h	28 km/h



COMPACT

## 1.33B WHEEL LOADER 4WS BACKHOE LOADER

	1.33B LOADER	1.33B BACKHOE LD.
Max. power	52 HP	52 HP
Breakout force	2.560 kg	2.560 kg
Static tipping load - Full turn	1.500 kg	1.500 kg
Bucket min/max	0.4 m <sup>3</sup>	0.4 m <sup>3</sup>
Max. permissible weight	4.000 kg	4.000 kg
Tyres	10.0/75 - 15.3	10.0/75 - 15.3
Forks load capacity (EN 474-3)	950 kg	950 kg
Max. speed	20 km/h	20 km/h
Max. digging depth, standard/telesc.	--	2.75 - 3.25 m



## 10.33B / C

4WS  
BACKHOE LOADER

	10.33B	10.33C
Max. power	105 HP	106 HP
Breakout force	9.100 kg	9.100 kg
Static tipping load - Full turn	5.600 kg	5.600 kg
Bucket min/max	1.2 - 1.5 m <sup>3</sup>	1.2 - 1.5 m <sup>3</sup>
Max. permissible weight	9.400 kg	9.400 kg
Tyres	405/70 - R24	405/70 - R24
Forks load capacity (EN 474-3)	3.700 kg	3.700 kg
Max. speed	38 km/h	40 km/h
Max. digging depth, standard/telesc.	4.8 - 5.8 m	4.8 - 5.8 m



## 10.23C / D

ARTICULATED BACKHOE LOADER

	10.23C	10.23D
Max. power	117 HP	106 HP
Breakout force	9.700 kg	10.800 kg
Static tipping load - Full turn	5.800 kg	5.800 kg
Bucket min/max	1.3 - 1.6 m <sup>3</sup>	1.3 - 1.6 m <sup>3</sup>
Max. permissible weight	9.920 kg	9.920 kg
Tyres	17.5 - L 24	17.5 - L 24
Forks load capacity (EN 474-3)	3.700 kg	3.700 kg
Max. speed	38 km/h	40 km/h
Max. digging depth, standard/telesc.	5.0 - 6.0 m	5.0 - 6.0 m



## 8.23E / F

ARTICULATED BACKHOE LOADER

	8.23E	8.23F
Max. power	105 HP	106 HP
Breakout force	6.900 kg	6.900 kg
Static tipping load - Full turn	4.950 kg	4.950 kg
Bucket min/max	1.1 - 1.4 m <sup>3</sup>	1.1 - 1.4 m <sup>3</sup>
Max. permissible weight	8.490 kg	8.490 kg
Tyres	16/70 - 24	16/70 - 24
Forks load capacity (EN 474-3)	3.120 kg	3.120 kg
Max. speed	40 km/h	40 km/h
Max. digging depth, standard/telesc.	4.6 - 5.4 m	4.6 - 5.4 m