


# EUROLINER

The Best  
Road/Field  
Compromise



## SURPRISING AGILITY

### HYDRO-TRIDEM

The "Hydro-Tridem" triple-axle concept combines the advantages of the triple axle suspension with leaves (axles that can easily be pulled over obstacles) and the hydraulic suspension (high sensitivity and great 250 mm clearance).

### HITCHING SUSPENSION

The standard hydropneumatic drawbar, together with the Hydro-Tridem concept, ensures an outstanding driving comfort.

### FRONT LIFTING AXLE

The EUROLINER are standard fitted with a front lifting axle allowing:

- in the fields, to transfer weight in order to have some more on the eyelet and therefore a better grip of the tractor;
- on the roads and only when unloaded, to reduce the wear to tyres.



## GENERAL POINTS

The independent supporting structure is made up of a narrow universal chassis "leaning" on the tank.

The EUROLINER is designed to be practical both on roads and in the fields. In this respect, this vehicle has an extensive standard equipment aiming at a high safety and driving comfort level, like a double forced steering axle that provides an outstanding driveability and a surprising agility in the field.



## SPECIFICATIONS

Structure width at the running gear	900 mm
Max. wheel dimensions	Ø 1,820 mm / width 800 mm <sup>(1)</sup>
Running gear	Hydro-Tridem
Drawbar	Hydropneumatic
Pumping systems	All types (except spiral pump)
Filling tools	All types
Rear implements	All types <sup>(2)</sup>

*(1) With recessing if required - (2) Suited to the dimensions of the vehicle*

## EUROLINER MODELS

Models	Theoretical capacity (l)	Axle(s): □ (mm) - track (mm) - studs	Brakes (mm)	Stand	Tank Ø (mm)
18000 TRS	18,331	ADR 3x130x2100-10S	406 x 120	Hydr. skid (DA) with direct connection to the tractor	2,000
20000 TRS	20,428	ADR 3x130x2100-10S	406 x 120	Hydr. skid (DA) with direct connection to the tractor	2,100
22500 TRS	22,587	ADR 3x150x2100-10S	420 x 180	Hydr. skid (DA) with direct connection to the tractor	2,100
24000 TRS	24,470	ADR 3x150x2100-10S	420 x 180	Hydr. skid (DA) with direct connection to the tractor	2,100
26000 TRS	26,200	ADR 3x150x2100-10S	420 x 180	Hydr. skid (DA) with direct connection to the tractor	2,100
28000 TRS	28,331	ADR 3x150x2100-10S	420 x 180	Hydr. skid (DA) with direct connection to the tractor	2,100

*NB: the capacity can vary according to the optional equipment (recessing in case of large or big wheels, filling arm, etc.).*



EVOLINE

JOSKIN