

V275

COMPACT LOADERS

GEHL®



KEY FEATURES

- ✓ Color Display with Keyless Start + Security Code
- ✓ Pilot Joystick Controls
- ✓ Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- ✓ Auxiliary Hydraulics with Drain Case
- ✓ LED Work, LED Rear Lights + Egress Lighting
- ✓ Vertical Lift Arm for More Reach at Dump Height
- ✓ Hydraglide™ Ride Control
- ✓ Greasable Pins for Reduced TCO
- ✓ Flip-Up Cooler with Hydraulic Fan
- ✓ Backup Alarm

KEY SPECIFICATIONS

- ✓ Operating Capacity (50%) - 1247 kg (2,750 lbs.)
- ✓ Overall height to top of ROPS - 2058 mm (81")
- ✓ Gross Power - 53.7 kW (72 hp)
- ✓ 294 Nm (217 ft.-lbs.) @ 1800 rpm max torque
- ✓ 3277 mm (129") height to hinge pin
- ✓ 1712 mm (67.4") machine width - less bucket
- ✓ 3774 kg (8,320 lbs.) operating weight

		METRIC
CAPACITIES	Operating Capacity At 50% Tipping Load	1247.37 kg
	Operating Weight	3719 kg
	Unladen weight	3371 kg
	Tipping capacity	2495 kg
WEIGHT AND DIMENSIONS	Wheelbase	1219 mm
	Overall Operating Height - Fully Raised	4252 mm
	Height to Hinge Pin - Fully Raised	3277 mm
	Overall Height to top of ROPS	2058 mm
	Dump angle at full height	42 °
	Dump height	2489 mm
	Overall length with bucket	3810 mm
	Dump reach - Full height	830 mm
	Rollback Angle at Full Height	92 °
	Seat to ground height	978 mm
	Overall width less bucket	1712 mm
	Ground clearance	209 mm
	Overall length - Less Bucket	3023 mm
	Clearance Radius - Front with Bucket	2289 mm
Rear departure angle	30 °	
PERFORMANCES	Travel speed (unladen)	11.40 km/h
	Travel Speed with Two-Speed Option - Maximum	17.50 km/h
ENGINE	Engine brand	Yanmar
	Engine model	4TNV98CT-XNGL
	Engine norm	Stage V
	Max. torque / Engine rotation	294 Nm / 1800 rpm
	Power source	Diesel
	Number of cylinders	4
	Engine power (Hp / kW)	72 Hp / 53.70 kW
	Engine cooling system	Water
	Battery voltage	12 V
	Alternator - Ampere	100 A
Starter	3 kW	
HYDRAULICS	Standard flow - Auxiliary hydraulics	98.40 l/min
	Auxiliary Hydraulic Pressure	239.59 bar
	High-Flow Auxiliary Hydraulics - Option	126 l/min
	High-Flow Auxiliary Hydraulics Pressure - Option	229.25 bar
TANK CAPACITIES	Fuel	106 l
	Hydraulic tank capacity	22.70 l
	Displacement	3.30 l
	Cooling liquid	18 l

GEHL Company reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. GEHL reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



STANDARD FEATURES

- 12Volt Power Port
- All-Tach® Attachment Mounting System
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Back-Up Alarm
- Battery Disconnect
- Brake Control (Auto/Manual)
- Cup Holder
- Engine Auto-Shutdown System
- Engine Block Heater
- Foot Throttle
- High-Back Adjustable Seat
- Horn
- Hydraglide™ Ride Control
- Hydraloc™ Safety System
- Hydrostatic Drive - Servo
- Lift Arm Support Device
- Operator Restraint Bar
- Pilot Joystick Controls

OPTIONAL FEATURES

- Adaptive air suspension heated fabric seat - With electric lumbar adjustment - GRAMMER
- Cabin with Heat and Air Conditioning
- Counterweight
- Electronic Attachment Control - 14-Pin Connector
- Engine Block Heater
- High-Flow Auxiliary Hydraulics
- IdealAccess™ Fold-Up Door
- LED front road lights
- Power-A-Tach® Attachment Mounting System
- Rearview Camera
- Sliding Side Windows



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT