

V325

COMPACT LOADERS

GEHL®



KEY FEATURES

- ✓ NEW Color Display with Keyless Start + Security Code
- ✓ NOW STANDARD Pilot Joystick Controls
- ✓ NEW Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- ✓ Variable Hydraulics with Drain Case
- ✓ NEW LED Work, LED Rear Lights + Egress Lighting



		METRIC
CAPACITIES	Operating Capacity At 50% Tipping Load	1474 kg
	Rated Operating Capacity with Optional Counterweight	1565 kg
	Operating Weight	4128 kg
	Tipping capacity	2948 kg
WEIGHT AND DIMENSIONS	Wheelbase	1353.82 mm
	Overall Operating Height - Fully Raised	4389 mm
	Height to Hinge Pin - Fully Raised	3409 mm
	Overall Height to top of ROPS	2084 mm
	Dump angle at full height	41 °
	Dump height	2634 mm
	Overall length with bucket	3922 mm
	Dump reach - Full height	846 mm
	Rollback at ground	29 °
	Rollback Angle at Full Height	94 °
	Seat to ground height	1039 mm
	Overall width less bucket	1852 mm
	Bucket Width	1880 mm
	Ground clearance	209 mm
Overall length - Less Bucket	3124 mm	
Clearance Radius - Front with Bucket	2299 mm	
PERFORMANCES	Travel speed (unladen)	10.70 km/h
	Travel Speed with Two-Speed Option - Maximum	17.30 km/h
WHEELS	Standard tires	12 x 16.5
ENGINE	Engine brand	Yanmar
	Engine model	4TNV98CT-9NGL
	Max. torque / Engine rotation	294 Nm / 1800 rpm
	Power source	Battery
	Engine power (Hp / kW)	72 Hp / 51.70 kW
	Starter	3 kW
HYDRAULICS	Standard flow - Auxiliary hydraulics	94.60 l/min
	Auxiliary Hydraulic Pressure	237.86 bar
	High-Flow Auxiliary Hydraulics - Option	128.70 l/min
	High-Flow Auxiliary Hydraulics Pressure - Option	229.25 bar
TANK CAPACITIES	Fuel	106 l
	Hydraulic tank capacity	30.30 l

GEHL Company reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. GEHL reserves the right to add improvements or make changes in specifications at any time without notice or obligation.

STANDARD FEATURES

- 12Volt Power Port
- All-Tach® Attachment Mounting System
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Back-Up Alarm
- Battery Disconnect
- Brake Control (Auto/Manual)
- Cup Holder
- Engine Auto-Shutdown System
- Engine Block Heater
- Foot Throttle
- High-Back Adjustable Seat
- Horn
- Hydraglide™ Ride Control
- Hydraloc™ Safety System
- Hydrostatic Drive - Servo
- Lift Arm Support Device
- Operator Restraint Bar
- Pilot Joystick Controls

OPTIONAL FEATURES

- Adaptive air suspension heated fabric seat - With electric lumbar adjustment - GRAMMER
- Cabin with Heat and Air Conditioning
- Counterweight
- Electronic Attachment Control - 14-Pin Connector
- Engine Block Heater
- High-Flow Auxiliary Hydraulics
- IdealAccess™ Fold-Up Door
- LED front road lights
- Power-A-Tach® Attachment Mounting System
- Rearview Camera
- Sliding Side Windows



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT